BLACKNITE®

P1229.1603

WBM Drilling

Product Description

BlacKnite® is a multi-sized particle, multi-blended dispersed coupled gilsonite, lignite and carbon black in a proprietary formulated glycol based liquid that has a primary function to prevent stuck pipe, reduce fluid loss and create a borehole condition that is not only stable, but stronger with exceptional HPHT fluid loss control.

Product Function

BlacKnite® is used to prevent stuck pipe, reduce fluid loss and create a borehole condition that is not only stable, but stronger with exceptional HPHT fluid loss control.

Features and Benefits

HPHT and dynamic fluid loss control - Improved filter cake texture and compaction - Enhances borehole stability - Provides broad PSD for micro-fracture sealing - Assists in sealing depleted formations - Aids in reactive shale stability - Enhances rheology control - Non-toxic - Environmentally safe - Non-sheening - Compatible with most water based fluids

Recommended Treatment

BlacKnite® can be mixed directly in mud systems. Additions of BlacKnite® are best accomplished by adding the product directly to the suction tank or through the rig hopper; however, the product can be added as a chemical pre-mix when necessary.

International Shipping References

Transportation of BlacKnite® is not restricted by any regulatory agency.

Standard Packing

BlacKnite® is available in 55-gallon (208 L) drums, 275-gallon (1,041 L) totes, 550-gallon (2.082 L) bulk containers or disposable tote tanks.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Liquid
- Reservoir Compatible: Non-Reservoir
- Sub Category: Sulphonated Asphalt
- SG value: 1.15
- Specific Gravity (25 ?C): 1.08
- Max Temperature: 350
- Category: Shale Stabilizers
- Product Tier: Premium
- Appearance: Black Liquid Dispersion
- Pour Point: -20 ?C

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE

PETROCHEM
DRILLING FLUIDS SOLUTIONS
A MAZRUI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.