CARBO FLAKES F (KOC)

P1530.2001

WBM/OBM Drilling

Product Description

Product Function

Features and Benefits

Recommended Treatment

International Shipping References

Standard Packing

Safe Handling Recommendations

Typical Physical Properties

- Physical State: Solid
- Reservoir Compatible: Both
- Sub Category: Calcium Carbonate
- SG value: 2.5
- Max Temperature: 350
- Category: LCM
- Product Tier: Premium

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE

PETROCHEM
DRILLING FLUIDS SOLUTIONS
A MAZRUI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.