# DMS

P1304.9305

OBM Drilling

## Product Description

DMS is a concentrated aqueous solution of a non-ionic surfactant used to enhance control of rheology and filtration properties of muds.

## Product Function

DMS is a chemically stable surfactant and simplifies the control of viscosity and gels. It has high tolerance to clay solids with minimum effect to viscosity.

## Features and Benefits

DMS aggregates mud solids into larger particles, reducing solids carry over into porous zones during initial formation of filter cake. Inter particle forces are reduced through reorientation of particles, thereby lowering gel strengths and yield points. It is compatible with all water base drilling fluid additives and is tolerant to salt, anhydrite or cement contamination. It will not degrade at any temperature anticipated in drilling. Exhibits thermal stability in excess of 400 ?F. It is non–damaging to equipment and poses no health risk in normal handling. It lubricates for reduced bit-balling and less differential sticking of drill pipe.

## Recommended Treatment

Stabilizing filtration rates will require treatments ranging from 80 – 350 L per 20 m3 of mud. Stabilizing flow properties of water-base mud, treatments will range from 15 to 250 L per 20 m3. Stabilizing drilling fluids at high temperature conditions will require dosages in the range of 100 to 400 L per 20 m3 of mud. The concentration of DMS™required to stabilize oil in water emulsions is in the range of 0.5– 2.0% and is dependent upon the amount and properties of the oil to be emulsified.

## International Shipping References

Transportation of DMS™ is not restricted by any regulatory agency.

## Standard Packing

DMS™ is packaged in 55 USG (208 liters) HDPE drum.

## Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

## Typical Physical Properties

- Physical State: Liquid
- Reservoir Compatible: Non-Reservoir
- Sub Category: Non-Ionic Surfactant
- SG value: 1
- pH (Neat): 5 - 7
- Flash Point: >100 ?C
- Max Temperature: 400
- Category: Detergents/Cleaners
- Product Tier: Regular
- Appearance: Colourless liquid
- Specific Gravity (25 ?C): 0.98 - 1.02

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE

PETROCHEM
DRILLING FLUIDS SOLUTIONS
A MAZRUI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.