GRAPHITE POWDER

P8003.2201

WBM/OBM Drilling

Product Description

GRAPHITE POWDER is` high performance synthetic graphite, specially sized and formulated to control loss circulation of drilling fluids.

Product Function

GRAPHITE POWDER is used as lost circulation additive for synthetic-based, oil–based and water–based fluids. It also helps in controlling partial and seepage losses and as solid lubricant in WBM in addition to liquids, for torque and drag reduction.

Features and Benefits

Will not plug downhole equipment at high concentrations. User is advised to consult with equipment or tool company before using extra coarse material. Maintains control on fluid losses and has been effective to reduce loss of slurries in cementing operations. Reduces torque and drag in tight holes, slide drilling and in landing casings. I increases strength / pressure gradient of weak formations. Provides excellent bridging and lubrication properties. Good prevention of differential sticking and stuck pipe. Very little effect on mud flow properties. Chemically inert; it can be mixed easily with water, oil and synthetic fluids and is compatible with fibers and mineral blends.

Recommended Treatment

The recommended treatment for partial losses is 20 to 50 lb/bbl (57 to 143 kg/m3). It can be used in combination with other lost circulation materials to control partial to severe losses.

International Shipping References

Transportation of GRAPHITE POWDER is not restricted by any regulatory agency.

Standard Packing

GRAPHITE POWDER is packaged in 25 kgs (55 lbs) sack.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Reservoir Compatible: Non-Reservoir
- Sub Category: Synthetic Graphite
- SG value: 1.7
- Specific Gravity: 1.70.
- Max Temperature: 400
- Category: LCM
- Product Tier: Regular
- Appearance: Black granular powder.
- Solubility in water: Soluble.

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE

PETROCHEM
DRILLING FLUIDS SOLUTIONS
A MAZRUI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.