

POLYLOSE C

P773.1601

Drilling/Completion

Product Description

POLYLOSE C main component is a modified cationic starch that reduces fluid loss in the MMO fluid without negatively affecting system performance or rheology. POLYLOSE C is effective in both fresh and salt water.

Features and Benefits

POLYLOSE C maintains and controls fluid loss and boosts system rheology without negatively affecting the MMO system. **It does not biodegrade.** It C acts as a colloidal blocking particle to prevent water movement. This process restricts the swelling and dispersion of cuttings and helps to reduce ultra fine solids build up. This product is effective at controlling fluid loss in both weighted and low solids drilling fluids over wide pH ranges. POLYLOSE C shows stability up to 275 °F (135 °C).

International Shipping References

Transportation of POLYLOSE C is not restricted by any regulatory agency.

Safe Handling Recommendations

Use normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 275
- Reservoir Compatible: Both
- Category: Fluid Loss/Sealing Additive
- Sub Category: MMO FL control
- Product Tier: Premium
- SG value: 1.5
- Appearance: off – white free flowing powder
- Moisture %: 10 max

Product Function

POLYLOSE C is a fluid loss reducer for the MMO mud system.

Recommended Treatment

POLYLOSE C concentration of 2.0–6.0 lb/bbl (5.7–17.1 kg/m³) is the normal range of treatment. Mix POLYLOSE C through the hopper at a rate of 5 to 10 minutes every 25 kgs sack. For best effect, POLYLOSE C should be added to the MMO system after calcium ions are removed using soda ash. Treatment rate should be determined on site or in test muds similar to planned field use.

Standard Packing

POLYLOSE C is packaged in 25 kgs multiwall paper sacks.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.