

QUICK THIN CLS

P418.0802

WBM Drilling

Product Description

Quick Thin CLS (Chrome lignosulphonate) is very effective to control the rheology of water based systems. It reduces the filtration and gel strength.

Features and Benefits

Quick Thin CLS is an effective deflocculant and rheology stabilizer for a wide range of water base drilling systems. Quick Thin CLS helps in fluid loss control without high concentrations of clay or filtration control agents. Quick Thin CLS is effective in scavenging soluble oxygen in circulating system. Quick Thin CLS is tolerant to presence of contaminants and is stable up to 350 ° F (176° C). Quick Thin CLS effectively inhibits bentonitic cuttings and shale hydration when used in sufficient concentrations. Quick Thin CLS contains the chrome in acceptable Cr⁺³ valance state.

International Shipping References

Transportation of Quick Thin CLS is not restricted by any regulatory agency.

Safe Handling Recommendations

Need only normal precautions for employee protection when handling chemical products. Appropriate respirator, gloves, goggles and apron need to be utilized. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Max Temperature: 350
- Reservoir Compatible: Non-Reservoir
- Category: Defloc./Thinners
- Sub Category:
- Product Tier: Regular
- SG value: 1.3
- Appearance: Dark Brown powder
- pH (1% solution): 2.5 - 4.5
- Bulk Density Kg/m³: 500 - 650

Product Function

Quick Thin CLS is effective in viscosity control and fluid loss reduction of all water based mud systems from fresh water to salt, lime, gypsum and potassium systems. Quick Thin CLS requires addition of caustic Soda or alternative alkaline material to maintain alkaline pH. For Lower pH systems, the product can be premixed in a higher alkalinity solution prior to being added to the active mud system.

Recommended Treatment

Normal treatment for Quick Thin CLS is 1.0 – 10.0 lbs/bbl (2.85 – 28.5 kgs/m³). Initial treatment usually ranges from 1.0 – 6.0 lb/ bbl (2.85 – 17.1 kg/m³) depending on the mud system, solids content.

Standard Packing

Quick Thin CLS is packaged in 50 lb (22.7 kgs) multiwall paper sacks.

+971 2 610 7000

info@ppc.ae | www.ppc.ae

Abu Dhabi | UAE



DRILLING FLUIDS SOLUTIONS
A MAZRAI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.