RESIPOL

P762.0402

WBM Drilling

Product Description

RESIPOL™ is synthetically formulated resinated lignite.

Product Function

RESIPOL™ is specially designed to provide filtration control and stabilizing rheological properties at high temperature.

Features and Benefits

RESIPOL™ is stable to temperatures in excess of 400 ?F. RESIPOL™ is equally effective in both fresh and sea water base drilling fluids and is tolerant to calcium contamination.

Recommended Treatment

RESIPOL™ is normally added in concentrations of 2 – 6 lb/bbl (6 – 17 kg/m³).

International Shipping References

Transportation of RESIPOL™ is not restricted by any regulatory agency.

Standard Packing

RESIPOL™ is packaged in 25 kgs multiwall paper sack.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Reservoir Compatible: Non-Reservoir
- Sub Category: Resinated Lignite
- SG value: 1.35
- Bulk Density Kg/m³: 700 - 900
- Max Temperature: 350
- Category: Filtration Control
- Product Tier: Premium
- Appearance: Dark free flowing powder
- pH (1% solution): 7 - 10

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE

PETROCHEM
DRILLING FLUIDS SOLUTIONS
A MAZRUI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.