SOLTEX E

P1208.2102

WBM/OBM Drilling

Product Description

SOLTEX E Additive is a sodium asphalt sulfonate made water soluble by a unique sulfonation process.

Product Function

It is a versatile, total mud conditioner that stabilizes shale formations, significantly increases lubricity, and lowers HTHP water loss. SOLTEX E enhances filter cake properties in both oil based and water-based muds.

Features and Benefits

Minimizes formation damage. Reacts with shale to prevent or stop sloughing and swelling. Significantly increases lubricity; either alone or synergistically with base oils. Environmentally acceptable: can be used on land and offshore. Extremely temperature stable: does not have the softening point typically associated with un-reacted asphaltic additives. Inhibits dispersion of drilled solids. Minimal and easily distinguishable fluorescence. Will not leave oil slick o sheen on water at offshore locations. No emulsifiers needed to ensure proper mixing.

Recommended Treatment

SOLTEX E is normally added in concentrations of 3–6 lb/bbl (8.5–17.2 kg/m3) to stabilize troublesome shales. Conventional hopper when chlorides do not exceed 60,000 ppm. When adding to high salinity systems, premixing SOLTEX E with fresh water by adding through chemical barrel will give best results. If mixing system requires, a defoamer may be added to prevent surface foam. SOLTEX E will be depleted by drilled solids and the wellbore face, then it is advisable to add 50% more product one day following the initial treatment to ensure adequate concentration.

International Shipping References

Transportation of SOLTEX E is not restricted by any regulatory agency.

Standard Packing

SOLTEX E is packaged in 50 lbs multiwall paper sack.

Safe Handling Recommendations

Utilize normal precautions for employee protection when handling chemical products. Utilize appropriate respirator, gloves, goggles and apron. Refer to the Material Safety Data Sheet (MSDS) for this product prior to use.

Typical Physical Properties

- Physical State: Solid
- Reservoir Compatible: Non-Reservoir
- Sub Category:
- SG value: 0
- Bulk Density Kg/m³: 800 - 1000
- Max Temperature: 0
- Category: Shale Stabilizers
- Product Tier: Regular
- Appearance: Dark brown to black free flowing powder

+971 2 610 7000
info@ppc.ae | www.ppc.ae
Abu Dhabi | UAE

PETROCHEM
DRILLING FLUIDS SOLUTIONS
A MAZRUI ENERGY SERVICES COMPANY

Petrochem Performance Chemicals Limited LLC believes in good faith that the information presented in this bulletin is accurate and reliable. No other representation or warranties are given or made in relation to the information or the products of whatsoever nature, and Petrochem Performance Chemicals Limited LLC assumes no responsibility for advice or recommendations made herein or any other information disseminated concerning this product. Petrochem Performance Chemicals Limited LLC will replace or issue credit for the purchase price of any product determined to be defective at delivery. Under no circumstances shall Petrochem Performance Chemicals Limited LLC or its responsible personnel be liable for any special or consequential damages whatsoever.